



Rubber cable H07RN-F3G1,5 black (L+N+PE)
terminated with NEUTRIK powerCON TRUE1 TOP connectors

- protection class: IP65
- max. current: 16A
- nominal voltage: 250V~
- operating temperatur: -25°C bis +55°C

Transperent shrink tube loose.
Unshrunked for customized self-labeling before shrinking.

The powerCON TRUE1 TOP is a connector with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live. (acc. IEC 60320-1 / DIN EN 60320-1 / VDE 0625-1)

Description	Stock-Code	Length	Weight
NKPH1-A1A1-M001	1027564	1 m	0,21 kg
NKPH1-A1A1-M002	1027565	2 m	0,34 kg
NKPH1-A1A1-M005	1027566	5 m	0,77 kg
NKPH1-A1A1-M010	1027567	10 m	1,48 kg
NKPH1-A1A1-M015	1027568	15 m	2,16 kg
NKPH1-A1A1-M020	1027569	20 m	2,89 kg

No.	Part	Qty.
1	Rubber cable H07RN-F3G1,5	1
2	NEUTRIK NAC3MX-W-TOP	1
3	NEUTRIK NAC3FX-W-TOP	1
4	Shrink Tube Ø 12,0 -> 3,0 / unshrunked	2
5	Shrinking tube / CX adress CE+WEE	1
6	Shrinking tube / nameplate	1

Note: cables < 2m only 1x shrink tube, cables >= 2m 2x shrink tubes

Sheet Number 1/1	Projection 	Scale 1:2	Format A4	Tolerancing ISO 2768-	
g	cm ²	cm ³	Created	HeBo	26.05.2021
Material			Modified	HeBo	10.06.2022
Material addition			Approved	DiRo	10.06.2022
Description NKPH1-A1A1 NEUTRIK powerCON TRUE1 Cables			ECN Number		
			Status	FOR FINAL	
NEUTRIK		3D Model ID	Document ID	Revision 04	