




Cable Datasheet

opticalCON[®] DUO ADVANCED



Technical Data Cables

Number of Fibers	2	2		
Fiber Type	Multimode	Single-mode		
Fiber standard	OM3	G.657A1		
Core Diameter	50 µm	9 µm		
Cladding Diameter	125 µm	125 µm		
Primary Coating Diameter	245 µm	245 µm		
Secondary Buffer Diameter	900 µm	900 µm		
Numerical Aperture	0.20	-		
Proof Test Level	100 kpsi	100 kpsi		
Wavelength	850 nm	1310 nm	1310 nm	1550 nm
Gigabit Ethernet Distance	1000 m	600 m	-	-
Attenuation	3.5 dB/km	1.5 dB/km	0.5 dB/km	0.5dB/km
Bandwidth	2000 MHz-km	500 MHz-km	-	-
Nominal Dispersion Slope	-	-	0.092 ps/(nm ² -km)	-
Refraction index	1.483	1.479	1.458	1.458
Cable Surface	V – jacket (black)	V – jacket (black)		
Jacket material	Polyurethane	Polyurethane		
Cable Weight	24 kg/km	24 kg/km		
Cable Diameter	5 mm	5 mm		
Installation (static):				
Max. Tensile Load	1800 N, short term	1800 N, short term		
Min. Bend Radius	50 mm	50 mm		
Operation (dynamic):				
Max. Tensile Load	600 N, short term	600 N, short term		
Min. Bend Radius	25 mm	25 mm		
Impact Resistance	1500 impacts (TIA/EIA 455-25A)	1500 impacts (TIA/EIA 455-25A)		
Crush Resistance	1800 N/cm (TIA/EIA-455-41A), short term	1800 N/cm (TIA/EIA-455-41A), short term		
Number of Conductors	-	-		
Nominal Core OD	-	-		
Conductor resistance	-	-		
Operation Temperature	-40°C to +85°C	-40°C to +85°C		
Storage Temperature	-70°C to +85°C	-70°C to +85°C		
Bend optimized	Yes	Yes		
Laser optimized	Yes	No		

Data subject to change without prior notice. © 2022 NEUTRIK[®]. NEUTRIK[®] are registered trademarks of Neutrik AG. ALL RIGHTS RESERVED.